

## SPECIFICATION of QUIET GRANULATOR



- Use “V type” cutting technology, decrease abrasion between blades and crushing chamber, improve service life of blades
- Outside structure of bearing
- Use self-aligning roller bearing
- Whole enclosed structure thus lower noise
- Use plug-in safety limit switch, improve safety performance of machines
- Choose twice dust collection devices, suitable to requirement of special dust-free

SPECIFICATION	MODEL	HGQ260-600F	
	HGQ260-500F	11 kW	15 kW
MOTOR POWER	11 kW	11 kW	15 kW
BLOWER POWER	0.75 kW	0.75 kW	2.2 kW
ROTATING SPEED	670 rpm	600 rpm	
ROTOR BLADE	6 pcs	6 pcs	
FIXED BLADE	2 pcs	4 pcs	
INFEED OPENING	260 x 500 mm	260 x 600 mm	
CRUSHING ROTARY SIZE	Ø260 x 500 mm	Ø260 x 600 mm	
SCREEN HOLE DIAMETER	Ø 10 mm	Ø 10 mm	
<b>EXT. DIMENSION</b>			
	L.	1460 mm	1560 mm
	W.	1190 mm	1190 mm
	H.	1640 mm	1640 mm
	L1.	1930 mm	2030 mm
	H0.	1040 mm	1040 mm
	H1.	1945 mm	1945 mm
	H2.	1415 mm	1415 mm
	ØD.	3 inch	3 inch

\*Note:

Throughputs will be varies depending on the material and screen hole diameter. The standard voltage is 3Phase, 380V, 50Hz. **We reserve the right to change specifications without prior notice. For special needs please let us know!**