

SPECIFICATION of SIDE-RECYCLING GRANULATOR



- Suitable for machine-side recycling to crush runner with easy operation, low noise and dust level
- Equipped with Motor Overload Protector
- Equipped with Main Power Isolated Switch and Chain Safety to protect operator and machine
- Cutter is made of special steel, sharp, wearable and crushing material with little dust
- Designed for modularized structure, easy to clean and do maintenance
- Installed with Four-wheel for easy moving

SPECIFICATION	MODEL	HFS-180	HFS-180-BJ
MOTOR POWER		1.5 kW	
BLOWER MOTOR		-	1.3 kW
ROTATING SPEED		355 rpm	
ROTOR BLADES		3 PCS	
FIXED BLADES		2 PCS	
OUTPUT		70 – 150 kg/h	
INFEED OPENING		140 x 180 mm	
CRUSHING ROTARY SIZE		Ø 150 x 180 mm	
SCREEN HOLE DIAMETER		Ø 6 mm	
WEIGHT		140 kg	160 kg
EXTERNAL DIMENSION			
	H. H1. H2. W. D. d1. Ød2.	1250 mm 1325 mm 1070 mm 530 mm 710 mm 785 mm 1.5"	1250 mm 1325 mm 1070 mm 795 mm 710 mm 785 mm 1.5"

*Note:

Throughputs will be varies depending on the material and screen hole diameter

The standard voltage is 3Phase, 380V, 50Hz.

We reserve the right to change specifications without prior notice. For special needs please let us know!