

RAPID COMPACT Metal separator for free-fall applications

- Detects and separates magnetic and non-magnetic metal contamination, even when enclosed in product
- Reduces expensive machinery failure and minimises production downtime
- Ensures product quality
- Prevents customer complaints
- Break even within a very short period of time



- Compact system with excellent price/performance ratio
- Minimum soace requirement and can be easily fitted into existing pipeline systems
- Standard Jacob adaptors for inlet and outlet ensure quick, hassle-free installation
- Minimal waste through "Quick-Flap" rejection system
- Easily accessible controls (sensitivity, rejection time, etc.) for "fine tuning" to site conditions easily accessible
- Enhanced signal-to-noise-ratio minimises electromagnetic pollution and vibrations



Sesotec GmbH Regener Straße 130 D-94513 Schönberg Germany Tel: +49 8554 308-0 Fax: +49 8554 2606 info@sesotec.com www.sesotec.com

Sesotec Partner (PLASTIC Division)

PT Mahkota Mas Mandiri Mulia Jakarta, Indonesia Tel. +62 815-1900-0269 info@ptmahkota.com www.ptmahkota.com



Metal separator RAPID COMPACT used for the quality control of plastic granulate

Scope of delivery:

- Compact unit with integral detection and rejection systems
- Control Unit MSG 3.4 K

Options/Accessories:

- Audible and visual alarm systems
- Feed hopper and filler inlet
- Magnet system to remove Fe contaminants
- Filter and regulator valve
- Air pressure monitor
- UL/CSA Certification
- Removable control unit

Typical Application Areas:


- Plastics industry, In-house recycling
- Recycling industry
- Wood industry
- · Chemical industry
- Feedingstuff industry

Product Description:

The RAPID COMPACT metal separator is used to inspect bulk goods under free-fall conditions. It detects all magnetic and non-magnetic metal contaminations (steel, stainless steel, aluminium) – even when enclosed in the product. Metal contaminations are rejected through the "Quick Flap" reject unit.

The RAPID COMPACT is used mainly in with low hygiene applications.

Function Chart:



 1) Infeed
 2) Detection coil
 3) Metal contaminant

 4) Separation flap
 5) Rejected material
 6) "Good" Material

Application:

- Machinery protection for extruders, blow moulding machines, fine grinding mills, after dosing (rotary valve, vibratory feed chutes)
- Quality control e. g. for pre-delivery inspection of incoming goods, granulate, reclaim, bagging stations, dryers and packing stations

If you need more detailed information ask for our technical data sheet or a discussion with our experienced Sesotec Sales team.